

Ch-4

:- Moving charges and Magnetism

NCERT Questions

1) A circular coil of wire consisting of 100 turns, each of radius 8.0 cm carries a current of 0.40 A. What is the magnitude of the magnetic field at the centre of the coil?

⇒ Number of turns on the circular coil, $n = 100$

Radius of each turn, $r = 8.0 \text{ cm} = 0.08 \text{ m}$

Current flowing in the coil, $I = 0.4 \text{ A}$

Magnitude of the magnetic field at the centre of the coil is given by the relation,

$$|B| = \frac{\mu_0}{4\pi} \frac{2\pi n I}{r}$$

Where,

$$\begin{aligned} \mu_0 &= \text{Permeability of free space} \\ &= 4\pi \times 10^{-7} \text{ TmA}^{-1} \end{aligned}$$

$$|B| = \frac{4\pi \times 10^{-7}}{4\pi} \times \frac{2\pi \times 100 \times 0.4}{0.08}$$

$$= 3.14 \times 10^{-4} \text{ T}$$

Hence, the magnitude of magnetic field is $3.14 \times 10^{-4} \text{ T}$.

2) A long & straight wire carries a current of 35 A. What is the magnitude of the field B at a point 20cm from the wire?

\Rightarrow Current in the wire, $I = 35 \text{ A}$

Distance of a point from the wire, $r = 20\text{cm} = 0.2\text{m}$

Magnitude of the magnetic field at this point is given as:

$$B = \frac{\mu_0}{4\pi} \frac{2I}{r}$$

where,

μ_0 = Permeability of free space $= 4\pi \times 10^{-7} \text{ T m A}^{-1}$

$$B = \frac{4\pi \times 10^{-7} \times 2 \times 35}{4\pi \times 0.2}$$

$$= 3.5 \times 10^{-5} \text{ T}$$

Hence, the magnitude of the magnetic field at a point 20cm from the wire is $3.5 \times 10^{-5} \text{ T}$.

3) A 30 cm wire carrying a current of 10 A is placed inside a solenoid perpendicular to its axis. The magnetic field inside the solenoid is given to be 0.27 T. What is the magnetic force on the wire?

\Rightarrow length of the wire, $l = 3\text{cm} = 0.03\text{m}$

Current flowing in the wire, $I = 10 \text{ A}$

Magnetic field, $B = 0.27 \text{ T}$

Angle between the current and magnetic field, $\theta = 90^\circ$

Magnetic force exerted on the wire is given as;

$$F = BIL \sin \theta$$

$$= 0.27 \times 10 \times 0.3 \sin 90^\circ$$

$$= 8.1 \times 10^{-2} \text{ N}$$

Hence, the magnetic force on the wire is $8.1 \times 10^{-2} \text{ N}$. The direction of the force can be obtained from Fleming's left hand rule

rule.

4.7) Two long and parallel straight wires A and B carrying currents of 8.0 A and 5.0 A in the same direction are separated by a distance of 4.0 cm. Estimate the force on a 10 cm section of wire A.

\Rightarrow Current flowing in wire A, $I_A = 8.0 \text{ A}$

Current flowing in wire B, $I_B = 5.0 \text{ A}$

Distance between the two wires, $d = 4.0 \text{ cm} = 0.04 \text{ m}$

length of a section of wire A, $L = 10 \text{ cm} = 0.1 \text{ m}$

Force exerted on length L due to the magnetic field is given as;

$$B = \frac{\mu_0 I_A I_B L}{4\pi d}$$

where,

μ_0 = Permeability of free space = $4\pi \times 10^{-7} \text{ T m A}^{-1}$

$$B = \frac{4\pi \times 10^{-7} \times 2 \times 8 \times 5 \times 0.1}{4\pi \times 0.04}$$

$$= 2 \times 10^{-5} \text{ N}$$

The magnitude of force is $2 \times 10^{-5} \text{ N}$. This is an attractive force normal to A towards B because the direction of the currents in the wires is the same.

Q8) A closely wound solenoid 80 cm long has 5 layers of windings of 400 turns each. The diameter of the solenoid is 1.8 cm. If the current carried is 8.0 A. A, estimate the magnitude of B inside the solenoid near its centre.

\Rightarrow length of the solenoid, $l = 80 \text{ cm} = 0.8 \text{ m}$
 There are five layers of windings of 400 turns each on the solenoid.

\therefore Total number of turns on the solenoid,
 $N = 5 \times 400 = 2000$

Diameter of the solenoid, $D = 1.8 \text{ cm} = 0.018 \text{ m}$

Current carried by the solenoid, $I = 8.0 \text{ A}$

Magnitude of the magnetic field inside the solenoid near its centre is given by the relation,

$$B = \frac{\mu_0 NI}{D l}$$

where,

$$\mu_0 = \text{Permeability of free space} = 4\pi \times 10^{-7} \text{ T m A}^{-1}$$

$$B = \frac{4\pi \times 10^{-7} \times 2000 \times 8}{0.018}$$

$$= 8\pi \times 10^{-3} = 2.512 \times 10^{-2} \text{ T}$$

Q1) In a chamber, a uniform magnetic field of 6.5 G ($1 \text{ G} = 10^{-4} \text{ T}$) is maintained. An electron is shot into the field with a speed of $4.8 \times 10^6 \text{ ms}^{-1}$ normal to the field. Explain why the path of the electron is a circle. Determine the radius of the circular orbit, ($e = 1.6 \times 10^{-19} \text{ C}$, $m_e = 9.1 \times 10^{-31} \text{ kg}$)

⇒ Magnetic field strength, $B = 6.5 \text{ G} = 6.5 \times 10^{-4} \text{ T}$
 Speed of the electron, $v = 4.8 \times 10^6 \text{ m/s}$
 Charge on the electron, $e = 1.6 \times 10^{-19} \text{ C}$
 Mass of the electron, $m_e = 9.1 \times 10^{-31} \text{ kg}$
 Angle between the shot electron and magnetic field, $\theta = 90^\circ$
 Magnetic force exerted on the electron in the magnetic field is given as :

$$F = evB \sin \theta$$

This force provides centripetal force to the moving electron. Hence, the electron starts moving in a circular path of radius R . Hence, centripetal force exerted on the electron,

$$F_c = \frac{mv^2}{R}$$

In equilibrium, the centripetal force exerted on the electron is equal to the magnetic force, i.e.

$$F_c = F$$

$$\frac{mv^2}{R} = evB \sin \theta$$

$$H = \frac{mv}{B \sin \theta}$$

$$= \frac{9.1 \times 10^{-31} \times 4.8 \times 10^6}{6.5 \times 10^{-4} \times 1.6 \times 10^{-19} \times \sin 90^\circ}$$

$$= 4.2 \times 10^{-9} \text{ m} = 4.2 \text{ cm}$$

Hence, the radius of the circular orbit of the electron is 4.2 cm.

4.12) In Exercise 4.11 obtain the frequency of revolution of the electron in its circular orbit. Does the answer depend on the speed of the electron? Explain.

⇒ Magnetic field strength, $B = 6.5 \times 10^{-4} \text{ T}$

Charge of the electron, $e = 1.6 \times 10^{-19} \text{ C}$

Mass of the electron, $m_e = 9.1 \times 10^{-31} \text{ kg}$

Velocity of the electron, $v = 4.8 \times 10^6 \text{ m/s}$

Radius of the orbit, $R = 4.2 \text{ cm} = 0.042 \text{ m}$

Frequency of revolution of the electron $= v$

Angular frequency of the electron $= \omega = 2\pi v$

Velocity of the electron is related to the angular frequency as:

$$v = R\omega$$

In the circular orbit, the magnetic force on the electron is balanced by the centripetal force. Hence, we can write:

$$evB = \frac{mv^2}{R}$$

$$evB = \frac{m}{R} (R\omega) = \frac{m}{R} (R2\pi v)$$

$$\omega = \frac{Be}{2\pi m}$$

This expression for frequency is independent of the speed of the electron. On substituting the known values in this expression, we get the frequency as:

$$\nu = \frac{6.5 \times 10^{-4} \times 1.6 \times 10^{-19}}{2 \times 3.14 \times 9.1 \times 10^{-31}}$$

$$= 18.2 \times 10^6 \text{ Hz}$$

$$= 18 \text{ MHz}$$

4.03) (a) A circular coil of 30 turns and radius 8.0 cm carrying a current of 6.0 A is suspended vertically in a uniform horizontal magnetic field of magnitude 1.0 T. The field lines make an angle of 60° with the normal of the coil. Calculate the magnitude of the counter torque that must be applied to prevent the coil from turning.

(b) Would your answer change, if the circular coil in (a) were replaced by a planar coil of some irregular shape that encloses the same area?

Ans (a) Number of turns on the circular coil, $n = 30$
Radius of the coil, $R = 8.0 \text{ cm} = 0.08 \text{ m}$

$$\text{Area of the coil} = \pi R^2 = \pi (0.08)^2 = 0.0201 \text{ m}^2$$

$$\text{Current flowing in the coil, } I = 6.0 \text{ A}$$

Magnetic field strength, $B = 1 \text{ T}$

Angle between the field lines and normal with the coil surface.

$$\theta = 60^\circ$$

The coil experiences a torque in the magnetic field. Hence, it turns. The counter torque applied to prevent the coil from turning is given by the relation,

$$T = NIBA \sin \theta \quad \dots \text{(i)}$$

$$= 30 \times 6 \times 1 \times 0.0201 \times \sin 60^\circ$$

$$= \underline{3.133 \text{ N m}}$$

(b) It can be inferred from relation (i) that the magnitude of the applied torque is not dependent on the shape of the coil. It depends on the area of the coil. Hence, the answer would not change if the circular coil in the above case is replaced by a planar coil of some irregular shape that encloses the same area.

4.5) Two concentric circular coils X and Y of radii 16 cm and 10 cm, respectively, lie in the same vertical plane containing the north to south direction. Coil X has 20 turns and carries a current of 16 A; coil Y has 25 turns and carries a current of -18 A. The sense of the current in X is anticlockwise, and clockwise in Y, for an observer looking at the coils facing west. Give the magnitude and direction of the net

magnetic field due to the coils at their centre.

$$\Rightarrow \text{Radius of coil } X, R_1 = 16 \text{ cm} = 0.16 \text{ m}$$

$$\text{Radius of coil } Y, R_2 = 10 \text{ cm} = 0.1 \text{ m}$$

$$\text{Number of turns of on coil } X, n_1 = 20$$

$$\text{Number of turns of on coil } Y, n_2 = 25$$

$$\text{Current in coil } X, I_1 = 16 \text{ A}$$

$$\text{Current in coil } Y, I_2 = 18 \text{ A}$$

Magnetic field due to coil X at their centre is given by the relation,

$$B_1 = \frac{\mu_0 n_1 I_1}{2R_1}$$

where,

$$\mu_0 = \text{Permeability of free space} = 4\pi \times 10^{-7} \text{ T m A}^{-1}$$

$$\therefore B_1 = \frac{4\pi \times 10^{-7} \times 20 \times 16}{2 \times 0.16}$$

$$= 4\pi \times 10^{-4} \text{ T (towards East)}$$

Magnetic field due to coil Y at their centre is given by the relation,

$$B_2 = \frac{\mu_0 n_2 I_2}{2R_2}$$

$$= \frac{4\pi \times 10^{-7} \times 25 \times 18}{2 \times 0.10}$$

$$= 9\pi \times 10^{-4} \text{ T (towards West)}$$

Hence, net magnetic field can be obtained as:

$$B = B_2 - B_1$$

$$\begin{aligned}
 &= 9\pi \times 10^{-4} - 4\pi \times 10^{-4} \\
 &= 5\pi \times 10^{-4} T \\
 &= 1.57 \times 10^{-3} T \text{ (towards west)}
 \end{aligned}$$

Q.15) A magnetic field of 100 G ($1 G = 10^{-4} T$) is required which is uniform in a region of linear dimension about 10cm and area of cross-section about $10^{-3} m^2$. The maximum current-carrying capacity of a given coil of wire is 15A and the number of turns per unit length that can be wound round a core is at most 1000 turns m^{-1} . Suggest some appropriate design particulars of a solenoid for the required purpose. Assume the core is not ferromagnetic.

\Rightarrow Magnetic field strength, $B = 100 G = 100 \times 10^{-4} T$
 Number of turns per unit length, $n = 1000 \text{ turns } m^{-1}$
 Current flowing in the coil, $I = 15 A$

Permeability of free space, $\mu_0 = 4\pi \times 10^{-7} T m A^{-1}$

Magnetic field is given by the relation,

$$B = \mu_0 n I$$

$$\therefore n I = \frac{B}{\mu_0}$$

$$= \frac{100 \times 10^{-4}}{4\pi \times 10^{-7}} = 7957.34$$

$$= 8000 A/m$$

If the length of the coil is taken as 50 cm, radius 4cm, number of turns 400, and current 10A, then these values are not unique for the given purpose. There is always a

possibility of some adjustments with limits.

Q.17) A toroid has a core of inner radius 25 cm and outer radius 26 cm, around which 3500 turns of a wire are wound. If the current in the wire is 11 A, what is the magnetic field (a) outside the toroid, (b) inside the core of the toroid and (c) in the empty space surrounded by the toroid.

$$\Rightarrow \text{Inner radius of the toroid } R_1 = 25 \text{ cm} = 0.25 \text{ m}$$

$$\text{Outer radius of the toroid, } R_2 = 26 \text{ cm} = 0.26 \text{ m}$$

$$\text{Number of turns on the coil, } N = 3500$$

$$\text{Current in the coil, } I = 11 \text{ A}$$

(a) Magnetic field outside a toroid is zero. It is non-zero only inside the core of a toroid.

(b) Magnetic field inside the core of a toroid is given by the relation,

$$B = \frac{\mu_0 N I}{l}$$

where,

$$\mu_0 = \text{Permeability of free space} = 4\pi \times 10^{-7} \text{ T m A}^{-1}$$

l = length of toroid

$$= 2\pi \left[\frac{R_1 + R_2}{2} \right]$$

$$= \pi (0.25 + 0.26)$$

$$= 0.51 \pi$$

$$\therefore B = \frac{4\pi \times 10^{-7} \times 3500}{0.51\pi} \times 11 \\ = 3.0 \times 10^{-2} T$$

(c) Magnetic field in the empty space surrounded by the toroid is zero.

4.18) (a) A magnetic field that varies in magnitude from point to point but has a constant direction is set up in a chamber. A charged particle enters the chamber and travels undeflected along a straight path with constant speed. What can you say about the initial velocity of the particle?

\Rightarrow The initial velocity of the particle is either parallel or anti-parallel to the magnetic field; hence, it travels along a straight path without suffering any deflection in the field.

(b) A charged particle enters an environment of a strong and non-uniform magnetic field varying from point to point both in magnitude and direction, and comes out of it following a complicated trajectory. Would its final speed equal the initial speed if it suffered no collision with the environment?

\Rightarrow Yes, the final speed of the charged particle will be equal to its initial speed. This is because magnetic force can change the

direction of velocity, but not its magnitude.

(i) An electron travelling west to east enters a chamber having a uniform electrostatic field in north to south direction. Specify the direction in which a uniform magnetic field should be set up to prevent the electron from deflecting from its straight line path.

→ An electron travelling from west to east enters a chamber having a uniform electrostatic field in the North-South direction. The moving electron can remain undeflected if the electric force acting on it is equal and opposite of magnetic field. Magnetic force is directed towards the south. According to Fleming's left hand rule, magnetic field should be applied in a vertically downward direction.